













## 1. CCTV Cameras





1.1 IR LED Cameras				
PICTURE	PRODUCT CODE	Specifications, functions	Unit price	
	IVT-540/36	IVT-540/36 IR LED camera 1/3" SHARP CCD, 540 TVL, color, Min. illumination: 0,1 Lux /F2.0, fixed 3.6 mm lens/F2.0 30 pcs IR-LED IR range: 25 m AGC, BLC S/N ratio: 48dB, Size: 59(W) x55(H) x90(D)mm 12 V DC IP 66 IDENTIVISION 1 year warranty	48,60	
	IVT-640E	IVT-640E IR LED camera 1/3" SONY EFFIO DSP, 650 TVL, color, Min. illumination: 0,01 Lux /F2.0, fixed 4 mm Daiwon lens/F2.0 30 pcs IR-LED IR range: 25 m AGC, BLC, 2D-NR S/N ratio: 48dB, OSD Menu Size: 107(W) x111(H) x163(D)mm 12 V DC 450 mA IP 66	79,00	
	IVT-4410VF	IVT 4410VF, IR LED camera 1/3" Sony CCD, DSP 480TVL, color, software DIN, 0.05 lux, IR LED max. 25m, varifocal: f=4.0-9.0mm (65°-31°), 12V DC. Software Day&Night, Color (0.1 lux), BW (0.05 lux), 36 pcs IR LED and 1 pcs light sensor, IR range: max. 25m, Built in varifocal lens: f=4.0-9.0mm/F1.5, Horizontal angle of view: 65°-31°, Zoom and focus adjustable from outside, on the back-side, AWB, AGC, BLC, S/N ratio: 48dB, IP66 protection, installable to outdoor, divided glass face, separate, dismantlable sunshield, 2-axis, cable managed, vandal-proof Bracket, Size: camera: 80.0(H.) x 85.0(W.) x 148.0 mm (L.), Bracket: 86.8(H.) x 52.4(W.) x 100.0 mm(L.), 12V DC, 400mA, Silver color, IDENTIVISION. 1 year warranty.	79,00	
	IVT-5410VFG	IVT 5410VFG, IR LED camera outdoor, 1/3", 540TVL, color, software DIN, 0.05 lux, IR LED max. 25m, varifocal: f=4.0-9.0mm (65°-31°), 12V DC. 1/3" Sony CCD, DSP, 540TVL, software Day&Night, color (0.1 lux), BW (0.05 lux), 42 pcs IR LED and 1db light sensor, IR range: max. 28m, Built in varifocal lens: f=4.0-9.0mm/F1.5, Horizontal angle of view: 65°-31°, Zoom and focus adjustable from outside, on the back-side, AWB, AGC, BLC, OSD set external S/N ratio: 48dB, IP66 protection, installable to outdoor, divided glass face, separate, dismantlable sunshield, 2-axis, cable managed, vandal-proof Bracket, Size: camera: 80.0(H.) x 85.0(W.) x 148.0 mm (L.), Bracket: 86.8(H.) x 52.4(W.) x 100.0 mm(L.), 12V DC, 400mA, Silver color, IDENTIVISION. 1 year warranty.	99,00	
	IVT-5420VF APACHE	IVT 5420VF APACHE camera with dual IR LED lighting 1/3" SONY CCD, color, 540 TVL, Software DIN Color(0.1 lux), B&W(0.05 lux), built in Varifocal lens 9.00-22 mm 12 pcs of POWER IR LED apart from the camera ,80 m IR range AES, AWB, BLC IP 66 225 x 152 x 90 mm, 2 kg 12V DC @ 1A IDENTIVISION. 1 year warranty	157,00	
	IVT-6520VF APACHE	IVT 6520VF APACHE camera, 650TVL with dual IR LED lighting 1/3" SONY EFFIO CCD, color, 650 TVL, Software DIN OSD Menu Color(0.1 lux), B&W(0.01 lux), built in Varifocal lens 9.00-22 mm 12 pcs of POWER IR LED apart from the camera ,80 m IR range AES, AWB, BLC, digital WDR, Eclipse (HLC), 2-DNR IP 66 225 x 152 x 90 mm, 1,5 kg 12V DC @ 1A IDENTIVISION. 1 year warranty	178,00	

 	IVT-6012VF	<p>IVT-6012VF Software D/N IR LED bullet camera with built-in Varifocal lens PREMIUM category, incl digital WDR 1/3" SONY Effio CCD 650 TVL Color (0.001 Lux), Black&amp;White IR LED ON (0.0 Lux) F1.2 42 pcs IR LED IR Range: max. 35 m Built-in varifocal lens: f=4.0-9.0mm/F1.2, Zoom&amp;focus set below bullet OSD 2D-DNR, digital WDR Motion detection ATW/AWC, AGC, BLC IP66 Outdoor protected 12V DC, 500mA IDENTIVISION. 1 year warranty</p>	103,00	
 	IVT-6011EVF/T	<p>IVT-6011 EVF/T Software D/N IR LED bullet camera with built-in Varifocal lens PREMIUM category, incl. digital WDR 1/3" SONY Effio CCD 650 TVL Color (0.1 Lux), Black&amp;White IR LED ON (0.0 Lux) F1.2 72 pcs IR LED IR Range: max. 50 m Built-in varifocal lens: f=9.0mm-22mm/F1.2, OSD Menu 2D-DNR,digital WDR Motion detection ATW/AWC, AGC, BLC IP66 Outdoor protected 12V DC, 700mA IDENTIVISION. 1 year warranty</p>	110,00	
 	IVT-6020VF	<p>IVT-6020VF True D/N IR LED bullet camera with built-in Varifocal lens PREMIUM category - 1/3" SONY CCD with HAWK-IV DSP, IR Cut filter - 600 TVL - Color (0.3 Lux), B&amp;W (0.001 Lux with DSS), IR LED ON (0.0 Lux) - 24 pcs long life, bright IR LED - IR Range: max. 30 m - Built-in varifocal lens: f=4.0-9.0mm/F1.2, 1,3 MP DCAI Zoom&amp;focus set external - OSD - 3D-DNR, Digital WDR - HSBLIC: High spotlight Suppression; used for car plate recognition - Motion detection - ATW/AWC, AGC, BLC - IP66 Outdoor protected - Elegant and practical unique all-directional adjusting cable managed bracket - 12V DC, max 800mA IDENTIVISION. 1 year warranty</p>	144,00	
<b>Box cameras</b>				
 	KPC-131	<p>KPC 131E 1/3" HR Color CCD, 500 TVL Low light sensitivity of 0.1 Lux at F2.0 Built-in microphone ATW,AGC,BLC DC12V / 80 mA AV TECH 2 years warranty</p>	52,00	
 	ICC-2560	<p>ICC-2560, 600 TVL box camera Color 1/3", 600TVL, software D/N, 0.08 lux, intelligent shutter controlling, DNR, digitális WDR, ECLIPSE (HLC), 12V DC.  Day/Night: software D/N (IR sensitive, adjustable). Illumination-color: 0.1 lux., BW: 0.01 lux. Electr Shutter: 1/50 ~ 1/100,000 sec AGC, BLC, 2-DNT, digital WDR, ECLIPSE OSD menu Privat zone masking, mirror function, motion detection Operating temp: -10 and +50°C Weight 400g. Consumption 12V DC, max. 100mA.  IDENTIVISION. 1 year warranty</p>	75,60	
 	ICC-2560-12/24	<p>ICC-2560-12/24, 600 TVL box camera, Color 1/3", 600TVL, software D/N, 0.08 lux, intelligent shutter controlling, DNR, digitális WDR, ECLIPSE (HLC), 12V DC.  Day/Night: software D/N (IR sensitive, adjustable). Illumination-color: 0.1 lux., BW: 0.01 lux. Electr Shutter: 1/50 ~ 1/100,000 sec AGC, BLC, 2-DNT, digital WDR, ECLIPSE OSD menu Privat zone masking, mirror function, motion detection Operating temp: -10 and +50°C Weight 400g. Consumption 12V DC / 24V AC., max. 100mA.  IDENTIVISION. 1 year warranty</p>	83,00	

1.3.		Dome Cameras		
	IFD-420	<p>IFD-420 minidome camera with 420 TVL            Sharp CCD, Software D/N, 420 TVL (752 x 582),            0,1 lux (F2.0),            ATW, AGC, DNR, SBLC,            Min illumination: 0,1 lux            Built in fixed 3.6 mm lens,            Angle of View(Diagonal) : 95.4' ~            12V DC            IDENTIVISION. 1 year warranty</p>	1/4"	<b>26,00</b>
	IFD-600	<p>IFD-600 minidome camera with 600 TVL            SONY CCD, Software D/N, 600 TVL (752 x 582),            0,1 lux (F2.0),            ATW, AGC, DNR, SBLC,            Min illumination: 0,1 lux            Built in fixed 3.6 mm lens,            Angle of View(Diagonal) : 95.4' ~            2 axis            12V DC            IDENTIVISION. 1 year warranty</p>	1/3"	<b>54,00</b>

1.4.		IR LED Dome Cameras	
Pictures	PRODUCT CODE	Specifications, functions	Unit price
	IVD-4410VF	<p>IVD 4410VF, IR LED dome camera  1/3" SONY CCD, DSP, 480TVL, software D/N, Indoor/outdoor, color, 0.05 lux, IR LED max. 20m, varifocal lens: f=4.0mm-9.0mm (65°-31°), 12V DC.  480TVL,  Software Day&amp;Night,  Color (0.1 lux), BW (0.05 lux),  36db IR LED and 1db light sensor, IR range max.: 20m,  Built in varifocal lens: f=4.0mm-9.0mm/F1.6, Horizontal angle of view: 65°-31°, Zoom and focus adjustable from outside,  AWB, AGC, BLC,  S/N ratio: 48db,  IP54 protection, 3-axis camera Bracket,  size: 119 (D.) x 82 mm (H.),  12V DC, 400mA,  Silver color,  IDENTIVISION. 1 year warranty.</p>	72,00
	IVD-5410VFG	<p>IVD 5410VFG, IR LED dome camera  1/3", 540TVL, software D/N, Indoor/outdoor, color, 0.05 lux, IR LED max. 20m, varifocal lens: f=4.0mm-9.0mm (65°-31°), 12V DC.  1/3" SONY CCD, DSP,  540TVL,  software Day&amp;Night, color (0.1 lux), BW (0.05 lux),  36 pcs IR LED and 1 pcs light sensor, IR range max.: 20m,  Built in varifocal lens: f=4.0mm-9.0mm/F1.6, horizontal angle of view: 65°-31°, Zoom and focus adjustable from outside,  AWB, AGC, BLC,  OSD Menu  S/N ratio: 48db,  IP 54 protection, massive outdoor dome housing, 3-axis camera bracket,  Size: 119 (D.) x 82 mm (H.),  12V DC, 400mA,  IDENTIVISION. 1 year warranty.</p>	83,00
	IVD-6010VF	<p>IVD 6010VF, IR LED dome camera  1/3", 600TVL, software D/N, Indoor/outdoor, color, 0.05 lux, IR LED max. 20m, varifocal lens: f=4.0mm-9.0mm (65°-31°), 12V DC.  1/3" SONY CCD, DSP,  600 TVL  software Day&amp;Night, color (0.1 lux), BW (0.01 lux),  36 pcs IR LED and 1 pcs light sensor, IR range max.: 35m,  Built in varifocal lens: f=4.0mm-9.0mm/F1.4, horizontal angle of view: 70°-42°, Zoom and focus adjustable from outside,  AWB, AGC, BLC, DNR, digital WDR, ECLIPSE (HLC)  OSD Menu  S/N ratio: 52db,  IP 55 protection, massive outdoor dome housing, 3-axis camera bracket,  Size: 119 (D.) x 82 mm (H.),  12V DC, 275mA,  IDENTIVISION. 1 year warranty.</p>	90,00
	IFD-5410I	<p>IFD-5410I, vandalproof IR LED dome camera  1/3" SONY CCD, DSP, 540TVL, software D/N, Indoor/outdoor, color, 0.05 lux,  500TVL,  Software Day&amp;Night, 22 pcs IR LED, 18 m IR range  0.2 lux / F2.0 (IR LED off)  Built in fixed lens: f=3.6mm, Horizontal angle of view: 95°.  AGC, BLC  S/N ratio: 48db,  IP66 protection,  size: 94 (D.) x 85 mm (H.),  12V DC, 260mA,  IDENTIVISION. 1 year warranty.</p>	48,60
	IFD-6010EVF	<p>IFD-6010EVF  Software D/N IR LED indoor dome camera with built-in Varifocal lens,  PREMIUM category  1/3" SONY Effio CCD  650 TVL  Color (0.001 Lux), Black&amp;White IR LED ON (0.0 Lux)  22 pcs IR LED  IR Range: max. 18 m  Built-in varifocal lens: f=4.0-9.0mm/F1.2, Zoom&amp;focus set below bullet  OSD Menu  Motion detection  ATW/AWC, AGC, BLC,2D-DNR, digital WDR  3 axis  12V DC, 500mA  IDENTIVISION. 1 year warranty</p>	79,00
<b>AV-TECH IR LED dome cameras</b>			
	KPC-133E/F36	<p>KPC133E/F36, IR LED dome camera.  1/3" Panasonic CCD, DSP,  500TVL,  Color (0.6 lux), BW (0.1 lux),  Software Day&amp;Night,  21 pcs IR LED and 1 pcs light sensor,  IR range: max. 15m,  Built in fixed lens: f=3.6mm/F2.0, Horizontal angle of view: 72°,  AWB, AGC, BLC,  S/N ratio: more than 48dB (AGC off).  3-axis,  Size: 94 mm (d) x 70 mm (h)  12V DC, 210mA,  AV TECH 2 years warranty</p>	50,00

		2.3 Varifocal AUTOIRIS (DC) lenses 1/3"		
PICTURE	PRODUCT CODE	Main Specifications, functions	Unit price	
 <a href="#">picture link</a>	<b>FUJINON 2.8-8mm</b> (YV2.8x2.8LA-SA2L)	FUJINON 2.8-8mm (YV2.8x2.8LA-SA2L), DC AI lens. 2.8-8.0mm/F0.95, 98°-33°, DC AI, varifocal. 1/3", varifocal, F=2.8-8.0mm/F0.95, horizontal angle of view: 98°-33°. CS mount, glass lens. FUJINON. 3 years warranty.	<b>39,60</b>	
<b>3. Digital Video Recorders</b>				
<b>3.1 Identivision E series DVRs</b>				
	PRODUCT CODE	BASIC FUNCTION DESCRIPTION, SPECIFICATIONS	Unit price	
 	<b>ICR-E42</b>	<b>ICR-E42 stand-alone H.264 DVR</b> <ul style="list-style-type: none"> <li>• 4 video input channel</li> <li>• Pentaplex : live, recording, playback, backup &amp; remote access</li> <li>• Stable Embedded LINUX operation system</li> <li>• Mouse control, IR remote control</li> <li>• Recording speed : D1 100 fps ( real time )</li> <li>• VGA &amp; video output is working paralel</li> <li>• VGA resolution is : (800x600, 1024x768, 1280x1024, 1360x768, 1440x900)</li> <li>• PTZ control by 18 protocol</li> <li>• Audio recording : 1 channel</li> <li>• Motion detection : 18 x 22 matrix</li> <li>• Prealarm</li> <li>• Built in IE Browser</li> <li>• Dual stream output ( QCIF/CIF for remote surveillance, D1 for local network)</li> <li>• Email sending at motion detection</li> <li>• Remote programming by LAN</li> <li>• Mobile remote surveillance : Support Windows mobile system, Symbian system, iPhone, Blackberry and Android system</li> <li>• HDD : max. 1 pc, 2 TB, Backsaving : USB, external DVD-RW</li> <li>• 1 hour video can be saved to USB stick within 15 minutes</li> <li>• Unique triple watchdog function, ensure equipment never crash</li> <li>• Hidden camera function</li> <li>• Central Monitoring Software : up to 255 pcs DVR</li> <li>• Multi language : English, Finnish, French, German, Greek, Hungarian, Italian, Polish, Portuguese, Russian, Spanish, Turkish</li> <li>• No fan = Silent operation , Small size &amp; weight = save freight cost ( 310x215x45 mm , 3 kg )</li> </ul> <b>IDENTIVISION 3 years warranty</b>	<b>138,60</b>	
 	<b>ICR-E83</b>	<b>ICR-E83 stand-alone H.264 DVR</b> <ul style="list-style-type: none"> <li>• 8 video Input channel</li> <li>• Pentaplex : live, recording, playback, backup &amp; remote access</li> <li>• Stable Embedded LINUX operation system</li> <li>• Mouse control, IR remote controller ( included )</li> <li>• Recording speed : 100/200/200, (D1/H01/CIF), optional adjustable fps per channel</li> <li>• 4 audio input</li> <li>• 8 alarm in, 1 alarm output</li> <li>• 2 video output</li> <li>• VGA &amp; video output is working paralel</li> <li>• VGA resolution is : (800x600, 1024x768, 1280x1024, 1360x768, 1440x900)</li> <li>• PTZ control by 18 protocol</li> <li>• Audio recording : 4 channel</li> <li>• Motion detection : 8 x 8 matrix</li> <li>• Prealarm</li> <li>• Instead of built in IE Browser, ActiveX download control</li> <li>• Dual stream output ( QCIF/CIF for remote surveillance, D1 for local network)</li> <li>• Email sending at motion detection (attaching pictures in CIF)</li> <li>• Remote programming by LAN</li> <li>• Mobile remote surveillance : Support Windows mobile system, Symbian system, iPhone, Blackberry and Android system</li> <li>• HDD : max. 1 pc, 2 TB, Backsaving : USB, external DVD-RW, SD card (max. 8 GB)</li> <li>• 1 hour video can be saved to USB stick within 15 minutes</li> <li>• Unique triple watchdog function, ensure equipment never crash</li> <li>• Hidden camera function</li> <li>• Central Monitoring Software : up to 255 pcs DVR</li> <li>• Multi language : English, Finnish, French, German, Greek, Hungarian, Italian, Polish, Portuguese, Russian, Spanish, Turkish</li> <li>• No fan = Silent operation , Small size &amp; weight = save freight cost ( 310x215x45 mm , 3 kg )</li> </ul> <b>IDENTIVISION 3 years warranty</b>	<b>208,80</b>	
 	<b>ICR-E163</b>	<b>ICR-E163 stand-alone H.264 DVR</b> <ul style="list-style-type: none"> <li>• 16 video Input channel</li> <li>• Pentaplex : live, recording, playback, backup &amp; remote access</li> <li>• Stable Embedded LINUX operation system</li> <li>• Mouse control, IR remote controller ( included )</li> <li>• Recording speed : D1 11fps/ch, CIF 400 fps real time</li> <li>• 4 audio input</li> <li>• 8 alarm in, 1 alarm output</li> <li>• 2 video output</li> <li>• VGA &amp; video output is working paralel</li> <li>• VGA resolution is : (800x600, 1024x768, 1280x1024, 1360x768, 1440x900)</li> <li>• PTZ control by 18 protocol</li> <li>• Audio recording : 1 channel</li> <li>• Motion detection : 18 x 22 matrix</li> <li>• Prealarm</li> <li>• Built in IE Browser</li> <li>• Dual stream output ( QCIF/CIF for remote surveillance, D1 for local network)</li> <li>• Email sending at motion detection</li> <li>• Remote programming by LAN</li> <li>• Mobile remote surveillance : Support Windows mobile system, Symbian system, iPhone, Blackberry and Android system</li> <li>• HDD : max. 1 pc, 2 TB, Backsaving : USB, external DVD-RW</li> <li>• 1 hour video can be saved to USB stick within 15 minutes</li> <li>• Unique triple watchdog function, ensure equipment never crash</li> <li>• Hidden camera function</li> <li>• Central Monitoring Software : up to 255 pcs DVR</li> <li>• Multi language : English, Finnish, French, German, Greek, Hungarian, Italian, Polish, Portuguese, Russian, Spanish, Turkish</li> <li>• Silent operation , Small size &amp; weight = save freight cost ( 310x215x45 mm , 3 kg )</li> </ul> <b>IDENTIVISION 3 years warranty</b>	<b>356,40</b>	

		3.2 IdentiVision H series DVRs		
	PRODUCT CODE	BASIC FUNCTION DESCRIPTION, SPECIFICATIONS	Unit price	
 	ICR-H41	<p>ICR-H41 stand-alone H.264 DVR</p> <ul style="list-style-type: none"> <li>• 4 video input channel</li> <li>• Pentaplex : live, recording, playback, backup &amp; remote access</li> <li>• Stable Embedded LINUX operation system</li> <li>• Mouse control, IR remote control</li> <li>• Recording speed : D1 100 fps ( real time )</li> <li>• VGA &amp; video output is working paralel</li> <li>• VGA resolution is : (800x600, 1024x768, 1280x1024, 1360x768, 1440x900)</li> <li>• Audio recording : 4 channel: 1 pcs VGA output; 1 video OUT, 1 audio OUT</li> <li>• Motion detection : 18 x 22 matrix, Prealarm, Built in IE Browser</li> <li>• Dual stream output ( QCIF/CIF for remote surveillance, D1 for local network)</li> <li>• Email sending at motion detection</li> <li>• Remote programming by LAN</li> <li>• Mobile remote surveillance : Support Windows mobile system, Symbian system, Iphone, Blackberry and Android system</li> <li>• HDD : max. 1 pc, 2 TB, Backsewing : USB,</li> <li>• 1 hour video can be saved to USB stick within 15 minutes</li> <li>• Unique triple watchdog function, ensure equipment never crash</li> <li>• Hidden camera function</li> <li>• Central Monitoring Software : up to 255 pcs DVR</li> <li>• Multi language : English, Finnish, French, German, Greek, Hungarian, Italian, Polish, Portuguese, Russian, Spanish, Turkish</li> <li>• No fan = Silent operation , Small size &amp; weight = save freight cost ( 310x215x45 mm , 3 kg )</li> </ul> <p>IDENTIVISION 3 years warranty</p>	107,80	
 	ICR-H81	<p>ICR-H81 stand-alone H.264 DVR</p> <ul style="list-style-type: none"> <li>• 8 video input channel</li> <li>• Pentaplex : live, recording, playback, backup &amp; remote access</li> <li>• Stable Embedded LINUX operation system</li> <li>• Mouse control, IR remote controller ( included )</li> <li>• Recording speed : 1. and 2. channel: D1 25 fps/ch, 3-8. channel CIF 25 fps/ch.</li> <li>• 4 audio input</li> <li>• 2 video output</li> <li>• VGA &amp; video output is working paralel</li> <li>• VGA resolution is : (800x600, 1024x768, 1280x1024, 1360x768, 1440x900)</li> <li>• Audio recording : 4 channel</li> <li>• Motion detection : 8 x 8 matrix</li> <li>• Prealarm</li> <li>• Instead of built in IE Browser, ActiveX download control</li> <li>• Dual stream output ( QCIF/CIF for remote surveillance, D1 for local network)</li> <li>• Email sending at motion detection (attaching pictures in CIF)</li> <li>• Remote programming by LAN</li> <li>• Mobile remote surveillance : Support Windows mobile system, Symbian system, Iphone, Blackberry and Android system</li> <li>• HDD : max. 1 pc, 2 TB, Backsewing : USB, SD card (max. 8 GB)</li> <li>• 1 hour video can be saved to USB stick within 15 minutes</li> <li>• Unique triple watchdog function, ensure equipment never crash</li> <li>• Hidden camera function</li> <li>• Central Monitoring Software : up to 255 pcs DVR</li> <li>• Multi language : English, Finnish, French, German, Greek, Hungarian, Italian, Polish, Portuguese, Russian, Spanish, Turkish</li> <li>• No fan = Silent operation , Small size &amp; weight = save freight cost ( 310x215x45 mm , 3 kg )</li> </ul> <p>IDENTIVISION 3 years warranty</p>	131,40	

## CENY VRÁTANE DPH

Vypracoval: Martin Bibko